



**Amerex Defense**

PO Box 81 Trussville AL 35173-0081

PH (205)655-5703 • FAX (205)661-4111

**MADE  
IN THE  
USA**

## Model 775

### 150 LB. Novec 1230™

### WHEELED FIRE EXTINGUISHER



- Environmentally friendly 3M™ Novec 1230™ Clean Agent (0 ODP - 1 GWP)
- Brass, chrome plated operating valve
- 125 PSI Operating Pressure
- Heavy duty steel cylinder, carriage and hose hanger assembly
- Lunette coupler for towing
- Quick release 40 ft. discharge hose with brass/chrome plated ball type shut-off nozzle
- Pressure gauge protected by a stainless steel gauge guard
- Corrosion resistant lime/yellow polyurethane paint finish
- Large color coded mylar instruction labels
- Aluminum UL label with barcoded serial numbers
- Operating temperature range: -65° to +120° F.
- 12 year prorated manufacturer's warranty

SPECIFICATIONS	150 LB. Novec 1230
Model Number	775
Agent	Novec 1230
Capacity (lbs.)	150
UL Rating	3A:80B:C
Shipping Weight (lbs.)	205 (empty) / 355 (filled)
Discharge Time (sec.)	22
Cylinder - DOT 4BW240	
Operating Press (psi)	125
Test Pressure (psi)	480
Burst Pressure (minimum - psi)	960
Discharge Range (ft.)	30
Safety Disc Burst Range (psi)	400 - 500
Hose Length (ft.)	40
Hose Diameter (in.)	.75
Wheels (Semi-pneumatic) (in.)	16 x 4
36" Rubberized Wheel Option	Available on Model 776R
Height (in.)	59
Width (in.)	29
Depth (in.)	42

NSN: 4210-01-610-6985