



Amerex Defense

PO Box 81 Trussville AL 35173-0081
 PH (205)655-5703 • FAX (205)661-4111



Model 320/321 2.5 lb Carbon Dioxide

RUGGED

- 5 Year Warranty
- All Metal Valve Construction
- MIL-STD-7905H Compliant Non-Shat Steel Cylinder
- Durable High Gloss Polyester Powder Paint
- Temperature Range -22°F to 120°F

BENEFIT

- Designed As Economical Drop-In Alternative to Currently Fielded Equipment (including bracket)
- Large Loop Stainless Steel Pull Pin

OPTION

- USCG Approved with Bracket Listed on UL Label

CARBON DIOXIDE is discharged as a white cloud of “snow” which smothers a fire by eliminating oxygen. It is effective for Class B flammable liquids and is electrically non-conductive. Carbon Dioxide is a clean, non-contaminating, odorless gas.



AGENT TYPE	CARBON DIOXIDE	
VALVE TYPE	CHROME PLATED BRASS	
DESIGN	HORN	
MODEL NUMBER	320	321
UL RATING	2B:C	2B:C
CAPACITY (LBS.)	2.5	2.5
SHIPPING WT. (LBS.)	8.9	8.9
HEIGHT (IN.)	13.25	13.25
WIDTH (IN.)	7.25	7.25
DEPTH (IN.)	14.38	14.38
RANGE (INITIAL- FT)	3 - 8	3 - 8
DISCHARGE TIME (SEC.)	9	9
FM APPROVED	NO	NO
INCLUDED BRACKET	WALL	896

Manufactured and Tested to ANSI/UL Standards
 Complies with NFPA 10 Standard
 ISO-9001 / ISO-14001 Certified
UL LISTED

CONFORMS TO TEST STANDARDS:

CAN/ULC-S503 - ANSI/UL154 &
 CAN/ULC-S508 - ANSI/UL711